CONDITION

Varnish poisoning

Varnish poisoning is illness caused by swallowing, breathing, or contacting harmful varnish ingredients.

WHAT IT IS
Toxic effects from swallowing, breathing, or contacting liquid varnish

BODY SYSTEM
Lungs, nervous system, digestive tract, skin, and eyes

MAIN SYMPTOMS
Coughing, breathing trouble, vomiting, dizziness

WHAT CAUSES IT
Exposure to varnish solvents or other toxic ingredients

HOW IT IS DIAGNOSED
Exposure history, examination, oxygen measurement, and targeted tests

MAIN TREATMENT
Decontamination, breathing support, and symptom-based hospital care

CAN IT BE CURED?
Yes - most limited exposures resolve with supportive care

IS IT AN EMERGENCY?
Sometimes - breathing trouble or reduced alertness needs emergency care

LONG-TERM OUTLOOK
Usually full recovery; severe exposure can cause lasting harm

Overview

Varnish poisoning means becoming unwell after swallowing varnish, breathing its fumes, or getting it on the skin or in the eyes. Varnish is a clear or coloured coating used to protect wood and other surfaces.

The risk depends on the product. Traditional and oil-based varnishes may contain hydrocarbons such as mineral spirits or turpentine. These are solvents that help the coating spread and dry. Some specialist products contain other harmful chemicals, including isocyanates in certain two-part polyurethane coatings. Water-based varnishes usually contain less solvent, but they should not be treated as harmless.

One of the main dangers after swallowing solvent-based varnish is aspiration. This means liquid enters the lungs, often during coughing or vomiting. It can inflame and damage lung

tissue, causing chemical pneumonitis.

If an exposure has just happened, use the product label and contact a poison information service. Do not wait for symptoms before seeking advice about swallowed varnish.

Symptoms

Symptoms depend on the ingredients, amount, route of exposure, and length of contact.

After swallowing varnish, possible symptoms include:

Breathing solvent vapour may cause eye, nose, and throat irritation. Higher concentrations can cause headache, nausea, confusion, unusual sleepiness, or loss of coordination. Poorly ventilated rooms increase this risk.

If varnish enters the lungs, coughing and breathing difficulty may begin quickly or develop over several hours. Other signs can include chest discomfort, fast breathing, wheezing, fever, or bluish lips. Fever after aspiration can result from chemical inflammation and does not always mean there is an infection.

Skin contact may cause redness, dryness, burning, or dermatitis, which is an irritated and inflamed skin rash. Eye exposure can cause watering, redness, pain, and blurred vision.

A major exposure may affect the brain, heart, or breathing. Severe drowsiness, collapse, seizures, an abnormal heartbeat, or stopped breathing require emergency care.

- Burning or irritation of the mouth and throat
- Nausea, vomiting, or stomach pain
- Coughing, choking, or a feeling that liquid went down the wrong way
- Drowsiness, dizziness, headache, or poor coordination

Causes and risk factors

Varnish poisoning is caused by contact with one or more harmful ingredients. The exact ingredients differ widely between products, so the container label or safety data sheet is important.

Solvent-based varnishes are generally more hazardous if swallowed or inhaled than water-based products. However, additives in any varnish may irritate the lungs, skin, or eyes. Two-part products can also contain a separate hardener with different risks.

Exposure may happen through:

Young children may drink from an open container or explore a spill. People who spray coatings can breathe finer droplets and vapour than people applying them with a brush. Repeated exposure to certain polyurethane hardeners may cause sensitisation, meaning even a small later exposure can trigger asthma-like symptoms.

- Accidental swallowing, particularly when varnish is stored in a drink container
- Breathing fumes while working in a small or poorly ventilated space
- Splashes to the eyes or prolonged contact with bare skin
- Repeated workplace exposure without suitable ventilation or protective equipment
- Deliberately inhaling solvent fumes

Diagnosis

There is no single test that confirms every type of varnish poisoning. Assessment begins with what happened, the product involved, when the exposure occurred, and any symptoms.

If it is safe to do so, take the container, label, or a clear photograph of it when seeking care. Do not carry a leaking or contaminated container in an enclosed vehicle. A poison specialist can use the product name and ingredient list to estimate its risks.

A medical assessment may include checks of breathing rate, alertness, heart rate, blood pressure, temperature, and blood oxygen. The mouth, skin, and eyes may also be examined.

People with coughing, low oxygen, or breathing difficulty may need a chest X-ray. Early X-rays can be normal, so the timing of symptoms also matters. Blood tests, an electrocardiogram to check heart rhythm, or other tests may be used after a significant exposure. Tests are chosen according to the product and symptoms rather than performed routinely in every case.

Treatment and management

Immediate first aid depends on how exposure occurred.

If varnish was swallowed, do not make yourself or anyone else vomit. Vomiting increases the chance that solvent will enter the lungs. Wipe away material left around the mouth and contact a poison information service promptly. Do not give food, drink, activated charcoal, or a home remedy unless a poison specialist advises it.

After breathing fumes, move into fresh air if this can be done without entering an unsafe space. Do not return to an area with strong vapours. Emergency responders may be needed for

a large spill or an enclosed area.

For skin exposure, remove contaminated clothing and wash the skin thoroughly with soap and water. Avoid using solvents to clean the skin because they can increase irritation.

For an eye splash, start rinsing immediately with clean, lukewarm running water. Remove contact lenses if they come out easily, and continue rinsing for at least 15 minutes. Persistent pain, blurred vision, or marked redness needs medical assessment.

There is no single antidote for most varnish poisoning. Hospital treatment is supportive, meaning it protects breathing and other body functions while the chemicals are cleared. It may include oxygen, monitoring, intravenous fluids, and treatment for wheezing, seizures, or other complications. A breathing tube and ventilator may be needed in severe cases.

Stomach emptying is generally avoided after hydrocarbon exposure because of the aspiration risk. Antibiotics and steroid medicines are not routinely used for uncomplicated chemical pneumonitis, although they may be appropriate for a separate problem identified during assessment.

Complications

The most important complication is chemical pneumonitis from varnish entering the lungs. Severe inflammation can reduce oxygen levels and, less commonly, progress to respiratory failure.

Other possible complications include:

Repeated workplace exposure to some ingredients can contribute to occupational asthma or continuing skin sensitivity. The likelihood of lasting harm is greatest after a large exposure, aspiration, prolonged unconsciousness, or delayed breathing problems.

- Ongoing airway irritation or wheezing
- Eye injury after prolonged chemical contact
- Abnormal heart rhythm after heavy solvent exposure
- Brain injury following prolonged lack of oxygen
- Skin inflammation from repeated contact

Prevention

Most varnish exposures can be prevented.

Keep varnish in its original, clearly labelled container. Never transfer it into a cup, bottle, food jar, or other container that someone could mistake for a drink. Store products closed, upright, and out of the sight and reach of children.

Read the label before use. Work outdoors or in a well-ventilated space, and follow product instructions about protective gloves, eye protection, and respiratory equipment. An ordinary face covering does not protect against solvent vapour.

Do not mix products unless the manufacturer specifically directs it. Keep varnish away from flames, sparks, cigarettes, and heat because many solvents are flammable.

At work, use the controls described in the safety data sheet and workplace risk assessment. Spraying and using two-part coatings may require specialist ventilation and protective equipment. Dispose of leftover products and solvent-soaked materials according to local hazardous-waste and fire-safety rules.

Living with it and what to expect

Many people with brief skin contact or mild fume irritation improve after washing or moving into fresh air. Symptoms may settle within hours, although irritated skin can take longer to recover.

After swallowing varnish, the main period of concern is the first several hours because lung symptoms can appear after the initial event. A poison service or medical team may recommend observation based on the product, amount, symptoms, and whether coughing or vomiting occurred.

Chemical pneumonitis may take days or weeks to settle. Follow-up can include checking cough, activity tolerance, oxygen levels, or chest findings. Most limited exposures do not cause an ongoing illness, but a severe lung or brain injury can have longer-lasting effects.

Repeated coughing, wheezing, or skin rashes linked to varnish work should not be accepted as a normal part of the job. An occupational health assessment can help identify the ingredient and reduce future exposure.

When to get medical help

Contact a poison information service promptly after varnish is swallowed, even if the amount seems small and there are no symptoms. Also seek advice after a substantial fume exposure, an uncertain exposure, or contact with an unfamiliar two-part product.

In the United States, Poison Control can be reached at 1-800-222-1222 . Elsewhere, use your local poison centre or urgent medical advice service.

Call emergency services now if the exposed person has:

Do not enter an enclosed, fume-filled area to rescue someone unless you have appropriate training and equipment. Call emergency services instead.

For non-emergency follow-up, arrange medical care if cough, wheezing, fever, dizziness, eye irritation, or skin inflammation continues or returns after the initial exposure.

- Trouble breathing, noisy breathing, or blue or grey lips
- Severe coughing or choking after swallowing varnish
- Confusion, collapse, a seizure, or difficulty waking
- Repeated vomiting with increasing sleepiness
- Severe chest pain
- Sudden loss of vision or severe eye pain

Common questions

What should I do if I swallowed only a small amount of varnish?

Do not make yourself vomit. Even a small amount of solvent-based varnish can be harmful if it enters the lungs. Contact a poison information service with the product name, ingredients, approximate amount, and time of exposure.

Can varnish fumes poison me?

Yes. Fumes can cause irritation, headache, nausea, dizziness, poor coordination, and drowsiness, especially in an enclosed space. Move to fresh air without putting yourself at risk. Breathing difficulty, confusion, or collapse requires emergency help.

How long does it take for symptoms to appear?

Irritation, dizziness, or choking may begin immediately. Lung inflammation after aspiration can become noticeable over several hours. This is why poison specialists may recommend monitoring even when someone initially appears well.

Is dried varnish still poisonous?

Fully cured varnish generally releases much less solvent than wet varnish. It should not be eaten or burned, however. Sanding can create irritating dust, and heating or burning a coating may release harmful fumes.

Is water-based varnish safe to swallow?

No. Water-based products often have lower solvent levels, but they can still contain irritating or harmful additives. Treat any swallowed varnish as a potential poisoning and contact a poison information service.

Should I drink milk or take activated charcoal?

Not unless a poison specialist specifically recommends it. Giving liquids may trigger vomiting, and activated charcoal does not work well for many hydrocarbons. The safest first step is product-specific advice.

Sources

- U.S. National Library of Medicine, MedlinePlus Medical Encyclopedia. "Varnish poisoning."
- National Capital Poison Center, Poison Control. "Paints and varnishes: Handle with care."
- MSD Manual Professional Edition. "Hydrocarbon Poisoning."
- Agency for Toxic Substances and Disease Registry. "Medical Management Guidelines for Stoddard Solvent."
- Royal Children's Hospital Melbourne. Clinical Practice Guideline: "Hydrocarbon poisoning."
- U.S. National Institute for Occupational Safety and Health. "Isocyanates."